

Vehicle Beacons

FACT SHEET

DICKE

Since 1886



TSMXDVAMB1BF



LPSM12AMBMGU



TSMR12AMBMGU

Features:

- All beacons feature a 360°, computer designed high clarity polycarbonate lens.
- Wind tunnel tested for security of attachment at speeds of up to 160 mph.
- **Lamp choices:** Xenon double flash or rotating Halogen.
- Rotating beacons run directly from the drive motor for quiet and efficient operation.
- **Mounting choices:** Magnetic or permanent.
- **Power supply choices:** Plug adapter or permanently wired.

Model	Description		W x H
LPSM12AMBMGU	MiniBEACON Xenon Tube	Magnetic Base - Plug Adapter	5.25" x 4.75"
TSMR12AMB1BF	TrafiBEACON Halogen	Rotating - Single Bolt - Wired	6.50" x 7"
TSMR12AMBMGU	TrafiBEACON Halogen	Rotating - Magnetic Base - Plug Adapter	7.25" x 7"
TSMXDVAMB1BF	Xenon BEACON Xenon	Double Flash - Single Bolt - Wired	6.5" x 7"
TSMXDVAMBMGU	Xenon BEACON Xenon	Dbl. Flash - Magnetic Base - Plug Adapter	7.25" x 7"



DICKE SAFETY PRODUCTS

www.dicketool.com

Illinois - 1201 Warren Avenue • Downers Grove, IL 60515 • Ph: 630.969.0050 • Fax: 630.969.3973
 Oregon - 1845 Anunsen Street, N.E. • Salem, OR 97301 • Ph: 800.333.5641 • Fax: 503.364.0340