

UniLAMPS™ and Beacons

UniLAMP™ Series 6-Volt 360° Incandescent Lights

- UniLAMP™ combines a 360° high clarity polycarbonate lens with an incandescent light source.
- Two versions are available, flashing and flashing with photocell.
- The yellow case is made of high impact polyethelene and comes with an integrated cone mounting bracket.
- Position-adjustable nut attached for bolt mounting.
- UniLAMP™ is powered by a 6 volt lantern battery (not included).
- Three lens colors available: amber, blue, and red.
- Standard package: 10 devices.
- Weight per carton: 13 lbs.



| | |
|----------------|----------------------------|
| UCW6N | Non-Photo Cell, Amber Lens |
| UCW6N-B | Non-Photo Cell, Blue Lens |
| UCW6N-R | Non-Photo Cell, Red Lens |
| UCW6S | Photo Cell, Amber Lens |
| UCW6S-B | Photo Cell, Blue Lens |
| UCW6S-R | Photo Cell, Red Lens |

Beacons



TSMR12AMBMGU



TSMXDVAMB1BF



LPSM12AMBMGU

- All beacons feature a 360°, computer designed high clarity polycarbonate lens.
- Wind tunnel tested for security of attachment at speeds of up to 160 mph.
- Lamp choices: Xenon double flash or rotating Halogen.
- Rotating beacons run directly from the drive motor for quiet and efficient operation.
- Mounting choices: Magnetic or permanent.
- Power supply choices: Plug adapter or permanently wired.

| | | | |
|---------------------|-----------------------|---|-------------------|
| LPSM12AMBMGU | MiniBEACON Xenon Tube | Magnetic Base, Plug Adapter | 5.25" x 4.75" ht. |
| TSMR12AMB1BF | TrafiBEACON Halogen | Rotating, Single Bolt, Wired | 6.50" x 7" ht. |
| TSMR12AMBMGU | TrafiBEACON Halogen | Rotating, Magnetic Base, Plug Adapter | 7.25" x 7" ht. |
| TSMXDVAMB1BF | Xenon BEACON Xenon | Double Flash, Single Bolt, Wired | 6.50" x 7" ht. |
| TSMXDVAMBMGU | Xenon BEACON Xenon | Dbl. Flash, Magnetic Base, Plug Adapter | 7.25" x 7" ht. |